1D Minstruments

The Thickness Gauge for High Loft Products has been designed to measure the thickness of high loft nonwoven material, by means of a digital readout. Thickness is determined by observing the linear distance that a moveable plane is displaced from a parallel surface by the specimen while under a specified pressure.

Thickness is one of the basic physical properties of Highloft Nonwoven fabrics. In certain industrial applications, the thickness may require rigid control within specified limits.

Applications:

- Highloft Nonwoven Fabric
- Textiles

Features:

- Accuracy: 0.1mmRange: 200mm x 0.01
- Mass: 288g
- Platform Scale: 2,000 x 1g
 Presser foot: 300mm x 300mm
 Sample Size: 300mm x 300mm
- Base Support Frame: 400mm x 400mm
- Digital Load Indicator
- Vertical Height Adjustment

Standards:

- ASTM D5736-95 (2001)
- ISO 9073-2

Options:

N/A

Connections:

 Electrical: 220/240 VAC @ 50 HZ or 110 VAC @ 60 HZ (please specify when ordering)



Dimensions:

H: 500mmW: 450mmD: 450mmWeight: 40kg

Benefits:

- Easy to use
- Fast results
- Accurate

10 - 11 Colrado Court Hallam, Victoria 3803 Australia Ph: +61 3 9708 6885 Fax: +61 3 9708 6770 Email: idm@idminstruments.com.au Web: www.idminstruments.com.au