

CREASE AND STIFFNESS TESTER

C0039 SERIES



IDM-C0039-M1, IDM-C0039-M2, IDM-C0039-M3



INTRODUCTION

Crease and stiffness testing of carton board, paper, printing and packaging materials are important measures to have correct and uniform quality. The board stiffness and crease recovery (spring back) is important in the performance of cartons on high-speed packaging machines and when manual folding. The value of crease stiffness is technically important in the folding of carton blanks during their erection and closure. The crease recovery (spring back) can result in forces, which distort the erected carton or cause stresses to be applied to closures, which reduce their effectiveness.

Crease and Stiffness Tester (IDM-C0039-M1)

The Model C0039 (M1) can determine the crease recovery by the decrease in resistance offered by creased board after it is folded 90° at the crease measuring the recovery force after 15 secs. Board Stiffness is determined by bending a 50mm length of board through a 15° angle.





Round 90° Crease Stiffness Tester (IDM-C0039-M2)

The C0039-M2 offers the same capabilities as the C0039, with the added functionality of being able to test for round corner creases. Round corners can be tested with ease using the easily changeable Round Corner Jaw. Folds are still able to be bent at 90°, and the Round Corner Jaw allows leeway for rounded corners to bend as intended. Another added functionality of the C0039-M2 is the ability to adjust the Load Bar position via the Load Bar Adjustment Knob, allowing for a range of different test lengths of 5mm, 10mm or 15mm creases.

Crease Stiffness Tester (IDM-C0039-M3)

Along with the above-mentioned features of the C0039 M1 & M2 model, C0039-M3 includes a digital display. The real-time display screen is the latest addition to the Stiffness Tester. The digital display is colour touch screen ensures simple operation making it convenient to check statistics, test reports and results. This product is the latest and most updated version available.



SPECIFICATIONS

Model	IDM-C0039-M1	IDM-C0039-M2	IDM-C0039-M3			
Range	0 – 10,000 gf (Gram Force)					
Bending Angle		90°				
Round Corner Bending	N/a	N/a Yes Yes				
Stiffness Bending	15°	N/a N/a				
Crease Stiffness Sample		38 x 36mm				
Board Stiffness Sample	70 x 38mm	N/a	N/a			
Accuracy	1 (+/- 0.5%)					
Test Time	15 seconds					
Check Weight	200g included					
RS 232 Output	Included					



1DM

OPTIONAL ITEMS

• IDM-C0039-OP1 - CST Data Acquisition Software (WinWedge Pro)

The IDM Crease and stiffness tester can be purchased with standard RS232 and software to automatically capture the output of results to a PC where stiffness/crease ratios can be calculated, test results saved, and test reports created and printed. This makes the CST even more easy to use with accurate precision results

- IDM-C0039-OP2 USB to RS-232 Cable
- IDM-C0039-OP3 Round Corner Jaw

Locat	ion		DM		Report Dy:	T. HALMOS	
Anh N			7576		Text Standard		BS5065
Serial	No:		TUA		Room Tempe	raturo:	21°C
Motor	Material Description		BOARD	Material C		fition:	
brownert	cursor v	ohere date to	he inserted b	minra tenting	Force Limits Upper Lower	Force (g) 1:0.0	
ID.	No.	Force (e)	Dute	Time	PawFuil	Initialy	Communite
The state of the s	1	15	20/03/2011	09 28 00 AM	Piene	TH	
E decree	2	16	2003/2011	09/20/10 AM	Pass	111	
	2	17	20/03/2011	OR 20:20 AM	Pegg	774	
A A	4	18	20/03/2011	00 28 30 AM	Pwww	TH	
	6	19	20/03/2011	09 28 40 AM	Pass	TH	
	U	20		09/20/00 AM		71.6	
	7	21		09.29.00 AM		774	
	8	22		09.29.10 AM		TH	
	9	23		09 29 20 AM		DH	
	10	24		DR ZR 30 AM		711	
	11	- 24	20/03/2011	08/38/30 VM	P000	111	
and the same and t	12						
	13						
	14						
	15						
	15						
	17						
	10						
	15						
· · · · · · · · · · · · · · · · · · ·	20						
THE RESERVE OF THE PARTY OF THE	21						
THE RESERVE OF THE PARTY OF THE	22						
The second secon	25						
	24						
The state of the s	35						
	20						
The state of the s	26						
	28						
	39						
	30						
	_						
- 10 - M	con	19.500	grams				
9 M	can	1.900	millinevitens				
SM. U	rosterved	3.020	4				
Ha	enge	9.000	grame				
Check None:	ved By:	T. HALMOS	tiignature:	180		Date:	20/03/2011

APPLICATIONS

- · Paper & Carton Board Manufacturers
- Ink & Coating
- · Packaging Manufacturers
- · Packaging Development

BENEFITS

- · Easy to use, dual purpose unit
- Increase production
- · Reduce waste
- · Increase packaging speeds

STANDARDS

- GB/T2679.3 Paper and Board–Determination of resistance to bending
- GB/T 23144 Paper and Board-Determination of bending stiffness by static methods Generation principle
- ISO2493 Paper and Board—Determination of resistance to bending
- ISO 5628 Paper and Board-Determination of bending stiffness by static methods Generation principle
- · BS6965-1 Creasing properties of carton board

CONNECTIONS

Electrical: 220/240 VAC @ 50 HZ

or

110 VAC @ 60 HZ

(please specify when ordering)

DIMENSIONS

Instrument:

- H: 200 mm
- W: 205 mm
- D: 260 mm
- Weight: 5.5 kg

Packaged:

- H: 420 mm
- W: 420 mm
- D: 440 mm
- · Weight: 8 kg

WARRANTY AND CALIBRATION SERVICES

- 1 year Warranty
- Our **Preventive Maintenance and Calibration (PM&C) program** has been designed to make the maintenance and calibration of your valuable testing equipment more cost effective by preventing breakdowns and downtime by regular calibration, service and replacement of defective parts. Talk to us about this today.



RELATED ITEMS

• IDM-C0016-M1 - Crease & Stiffness Cutter

IDM's precision cutter is designed to assist in the easy and accurate cutting of sample specimens for both crease stiffness and bending stiffness testing.

Samples prepared:

- Crease stiffness testing 38 x 36mm
- Board samples 70 x 38mmDimensions

Dimensions	H: 85mm x W: 95mm x D: 295mm	
Weight	3.5kg	





